



## SkyView SZT-8008 H.264 8 Channel Standalone DVR System



- H.264 Video Compression
- Triplex Operation: Playback, Record & Remote Network
- GUI, Support Highest Resolution 1280x1024
- PTZ Speed Dome Control support multi-protocols
- 2 Sata Hard Disk Interface
- NTP For Time Synchronization
- Motion Detection Maker
- DDNS Auto Setup and PPPoE
- ezBurn™ for Quick Video Export
- Auto Calculate Hard Disk Recording by Days/Frame/Quality
- Support Call Monitor
- VGA / Remote Control / Mouse
- Event Occurs Send Video Notification Via E-mail
- Support Multiple Languages
- Host & IE Browser PLAYBACK For 16 Channels Simultaneously
- Unique Central Management System

<b>Model</b>		<b>SZT-8008</b>
<b>Operation System</b>		Embedded Linux O.S.
<b>Video</b>	<b>Input</b>	BNC x 8, 1.0Vp-p, 75ohm
	<b>Output</b>	BNC x 1, 1.0Vp-p, 75ohm
	<b>VGA Output</b>	800 x 600, 1024 x 768, 1280 x 1024 pixels
	<b>Picture Refresh Rate</b>	NTSC: 240fps / PAL: 200fps
<b>Audio</b>	<b>Input</b>	x 8 Line-in, D-SUB
	<b>Output</b>	RCA x 1, 1 Channel Line-Out
	<b>Compression Method</b>	Proprietary
	<b>Data Rate</b>	8kb/s per Channel
<b>Recording</b>	<b>Compression Method</b>	H.264
	<b>Recording Mode</b>	Schedule, Alarm, Motion Detection
	<b>Pre-Alarm</b>	Yes
	<b>Recording, Resolution &amp; Rate</b>	NTSC: 60fps/720x480, 120fps/720x240, 240fps/360x240
	<b>Recording Mode</b>	5 levels presets
	<b>Image Size</b>	1K to 20K Byte/picture
	<b>Storage Mode</b>	Linear / Circular
<b>Storage</b>	<b>Internal</b>	x2 Sata2 HDD
	<b>External</b>	2 x USB2.0 Port for USB ThumbDrive, External CDRW or DVDRW
<b>Alarm</b>	<b>Alarm Input</b>	x8, D-Sub
	<b>Alarm Relay Output</b>	x1, D-Sub
	<b>Alarm Detection</b>	N.C. / N.O., Programmable
	<b>Motion Detection</b>	Adjustable 16 x 12 Grid Array, Sensitivity, Trigger Level
	<b>Video Loss Detection</b>	Programmable
<b>Communication</b>	<b>Network Connectivity</b>	Ethernet RJ45 connector 10/100Mbps, Support DHCP
	<b>Remote Control Software</b>	Yes
	<b>Remote Operation</b>	Monitor, Playback, Recording, System Setup & Archive
	<b>RS-485</b>	D-Sub
	<b>IR Remote</b>	Yes (Optional)
	<b>PTZ Control</b>	Pelco P , Pelco D , AD422, Fastrax 2 , Panasonic
<b>General</b>	<b>Dimension (mm)</b>	440(W) x 60(H) x 330(D)
	<b>Weight</b>	8 kg
	<b>Operation Temperature</b>	-5°C ~ 40°C
	<b>Relative Humidity</b>	5% ~ 95% Non-condensing
	<b>Power Consumption</b>	AC 100 ~ 240V, 50~60Hz, 60W Adaptor